

FM-3030X High-Power Free Standing Intermittent Duty Demagnetizer, 30" x 30" Opening

Item #: 15-01-10

Standard Features:

- 480VAC 60Hz 1-Phase Input, Other Voltages Available Upon Request
- 30" Wide x 30" Tall Opening Size
- 12,884 Ampere-Turn Rating
- Intermittent Duty Cycle
- Non Ferrous Coil Core Improves Efficiency
- NEMA 12 Electrical Enclosure
- Pilot Light for Line Power
- Adjustable Electronic Cycle Timer
- Push Buttons on Each Side to Start the Demag Cycle
- Automatic Resetting Thermal Overload Protection for Coil Protection
- Paint Color - Magwerks Tan Baked Industrial Powder Coating



Model shown above equipped with the optional Track and Carriage

- Optional Ring Down Bank Available Prevents Accidental Remagnetization of the Work
- Optional Field Retrofittable Track and Carriage or Table Tops Available

Standard Features and Options Subject to Change Without Notice

Standard Line Voltage & Current Requirements

VAC: 480, 60Hz, Recommended Service Size: 200, Fuse Type: 200A T/D
 Recommended Wire Size: 1/0AWG (Min.) without RDB For ≤100 Ft. of Run
 VAC: 480, 60Hz, Recommended Service Size: 60, Fuse Type: 60A T/D
 Recommended Wire Size: 6AWG with RDB For ≤100 Ft. of Run

Option Group

15-01-10-52-480:

Demag Disconnects with RDB

FM-3030X - 480V, Circuit Protected Disconnect When Equipped With RDB

Option Group

15-01-99-35:

Demag Forced Air Cooling

FM-3030 Series Forced Air Cooling

Option Group

15-01-10-53-20:

Demag Ring Down Banks, FM Series

FM-3030X 480V-60Hz RDB (Ring Down Bank)

Option Group

15-01-99-14:

Demag Track and Carriage

FM-3030 Track and Carriage